

# SiSU

Markup

Ralph Amissah

copy @ [www.jus.uio.no/sisu/](http://www.jus.uio.no/sisu/) \*

---

Copyright © Ralph Amissah 2007, part of SiSU documentation,  
License GPL 3

Generated by SiSU [ SiSU 0.59.0 of 2007w38/0 ] [www.jus.uio.no/sisu](http://www.jus.uio.no/sisu)

Copyright © 1997, current 2007 Ralph Amissah, All Rights Reserved.

SiSU is software for document structuring, publishing and search (with object citation numbering), [www.sisudoc.org](http://www.sisudoc.org)

SiSU is released under [GPL 3](http://www.gnu.org/licenses/gpl.html) or later, <<http://www.fsf.org/licenses/gpl.html>>.

Document information:

*sourcefile* [sisu\\_markup.sst](#)

Generated by SiSU [www.jus.uio.no/sisu](http://www.jus.uio.no/sisu)

version information: SiSU 0.59.0 of 2007w38/0

For alternative output formats of this document check:

<[http://www.jus.uio.no/sisu/sisu\\_markup/sisu\\_manifest.html](http://www.jus.uio.no/sisu/sisu_markup/sisu_manifest.html)>

# Contents

<b>SiSU - Markup, Ralph Amissah</b>	<b>1</b>
<b>SiSU Markup</b>	<b>1</b>
1. Introduction to SiSU Markup . . . . .	1
1.1 Summary . . . . .	1
1.2 Markup Examples . . . . .	2
2. Markup of Headers . . . . .	2
2.1 Sample Header . . . . .	2
2.2 Available Headers . . . . .	3
3. Markup of Substantive Text . . . . .	5
3.1 Heading Levels . . . . .	5
3.2 Font Attributes . . . . .	5
3.3 Indentation and bullets . . . . .	6
3.4 Footnotes / Endnotes . . . . .	6
3.5 Links . . . . .	7
3.6 Grouped Text . . . . .	8
4. Composite documents markup . . . . .	13
<b>Markup Syntax History</b>	<b>14</b>
5. Notes related to Files-types and Markup Syntax . . . . .	14
<b>Document Information (metadata)</b>	<b>15</b>
Metadata . . . . .	15
<b>Information on this document copy and an unofficial List of</b>	
<b>Some web related information and sources</b>	<b>16</b>
Information on this document copy . . . . .	16
Links that may be of interest . . . . .	16

# SiSU - MARKUP, RALPH AMISSAH

## SiSU MARKUP

### 1. Introduction to SiSU Markup<sup>1</sup>

#### 1.1 Summary

SiSU source documents are plaintext (UTF-8)<sup>2</sup> files

All paragraphs are separated by an empty line.

Markup is comprised of:

- at the top of a document, the document header made up of semantic meta-data about the document and if desired additional processing instructions (such an instruction to automatically number headings from a particular level down)

- followed by the prepared substantive text of which the most important single characteristic is the markup of different heading levels, which define the primary outline of the document structure. Markup of substantive text includes:

- heading levels defines document structure
- text basic attributes, italics, bold etc.
- grouped text (objects), which are to be treated differently, such as code blocks or poems.
- footnotes/endnotes
- linked text and images
- paragraph actions, such as indent, bulleted, numbered-lists, etc.

Some interactive help on markup is available, by typing `sisu` and selecting `markup` or `sisu -help markup`

<sup>1</sup> From sometime after SiSU 0.58 it should be possible to describe SiSU markup using SiSU, which though not an original design goal is useful.

<sup>2</sup> files should be prepared using UTF-8 character encoding

## 1.2 Markup Examples

### 1.2.1 Online

Online markup examples are available together with the respective outputs produced from [<http://www.jus.uio.no/sisu/SiSU/2.html>](http://www.jus.uio.no/sisu/SiSU/2.html) or from [<http://www.jus.uio.no/sisu/sisu\\_examples/>](http://www.jus.uio.no/sisu/sisu_examples/)

There is of course this document, which provides a cursory overview of sisu markup and the respective output produced: [<http://www.jus.uio.no/sisu/sisu\\_markup/>](http://www.jus.uio.no/sisu/sisu_markup/)

Some example marked up files are available as html with syntax highlighting for viewing: [<http://www.jus.uio.no/sisu/sample/syntax>](http://www.jus.uio.no/sisu/sample/syntax)

an alternative presentation of markup syntax: [<http://www.jus.uio.no/sisu/sample/on\\_markup.txt>](http://www.jus.uio.no/sisu/sample/on_markup.txt)

### 1.2.2 Installed

With **SiSU** installed sample skins may be found in: `/usr/share/doc/sisu/sisu_markup_samples/dfsg` (or equivalent directory) and if `sisu-markup-samples` is installed also under: `/usr/share/doc/sisu/sisu_markup_samples/non-free`

## 2. Markup of Headers

Headers consist of semantic meta-data about a document, which can be used by any output module of the program; and may in addition include extra processing instructions.

Note: the first line of a document may include information on the markup version used in the form of a comment. Comments are a percentage mark at the start of a paragraph (and as the first character in a line of text) followed by a space and the comment:

```
% this would be a comment
```

### 2.1 Sample Header

This current document has a header similar to this one (without the comments):

```
% SiSU 0.57
@title: SiSU
@subtitle: Markup
@copyright: Copyright (C) Ralph Amissah 2007, part of SiSU documentation, License GPL 3
@type: information
@subject: ebook, epubliing, electronic book, electronic publishing, electronic document, electronic citation,
data structure, citation systems, search
@date.created: 2002-08-28
@date.issued: 2002-08-28
@date.available: 2002-08-28
@date.modified: 2007-09-16
@date: 2007-09-16
@level: new=C; break=1; num_top=1
% comment: in this @level header num_top=1 starts automatic heading numbering at heading level 1 (num-
bering continues 3 levels down); the new and break instructions are used by the LaTeX/pdf and odf output to
determine where to put page breaks (that are not used by html output or say sql database population).
@skin: skin_sisu_manual
% skins modify the appearance of a document and are placed in a sub-directory under ./sisu/skin ~ ./sisu/skin
or /etc/sisu/skin. A skin may affect single documents that request them, all documents in a directory, or be
site-wide. (A document is affected by a single skin)
@bold: /Gnu|Debian|Ruby|SiSU/
```

@links: { SiSU Manual }[http://www.jus.uio.no/sisu/sisu\\_manual/](http://www.jus.uio.no/sisu/sisu_manual/)  
 { Book Samples and Markup Examples }<http://www.jus.uio.no/sisu/SiSU/2.html>  
 { SiSU @ Wikipedia }<http://en.wikipedia.org/wiki/SiSU>  
 { SiSU @ Freshmeat }<http://freshmeat.net/projects/sisu/>  
 { SiSU @ Ruby Application Archive }<http://raa.ruby-lang.org/project/sisu/>  
 { SiSU @ Debian }<http://packages.qa.debian.org/s/sisu.html>  
 { SiSU Download }<http://www.jus.uio.no/sisu/SiSU/download.html>  
 { SiSU Changelog }<http://www.jus.uio.no/sisu/SiSU/changelog.html>

44

**@publisher:****@contributor:**

45

**@translator:** [or @translated\_by:]

46

**@illustrator:** [or @illustrated\_by:]

47

**@prepared\_by:** [or @digitized\_by:]

48

**@date:** **2000-08-27** [ also @date.created: @date.issued:

49

@date.available: @date.valid: @date.modified: ]

**@type:** article

50

**@format:**

51

**@identifier:**

52

**@source:**

53

**@language:** [or @language.document:] [country code for language if available, or language, English, en is the default setting] (en - English, fr - French, de - German, it - Italian, es - Spanish, pt - Portuguese, sv - Swedish, da - Danish, fi - Finnish, no - Norwegian, is - Icelandic, nl - Dutch, et - Estonian, hu - Hungarian, pl - Polish, ro - Romanian, ru - Russian, el - Greek, uk - Ukrainian, tr - Turkish, sk - Slovak, sl - Slovenian, hr - Croatian, cs - Czech, bg - Bulgarian ) [however, encodings are not available for all of the languages listed.]

54

[@language.original: original language in which the work was published]

55

**@papersize:** (A4|US\_letter|book\_B5|book\_A5|US\_legal)

56

**@relation:**

57

**@coverage:**

58

**@rights:** Copyright (c) Name of Right Holder, all rights reserved, or as granted: public domain, copyleft, creative commons variant, etc.

59

**@owner:**

60

## 2.2 Available Headers

Header tags appear at the beginning of a document and provide meta information on the document (such as the Dublin Core), or information as to how the document as a whole is to be processed. All header instructions take either the form @headername: or 0~ headername. All Dublin Core meta tags are available

**@identifier:** information or instructions

where the “identifier” is a tag recognised by the program, and the “information” or “instructions” belong to the tag/identifier specified

Note: a header where used should only be used once; all headers apart from @title: are optional; the @structure: header is used to describe document structure, and can be useful to know.

This is a sample header

**% SiSU 0.38** [declared file-type identifier with markup version]

**@title:** [title text] This is the title of the document and used as such, this header is the only one that is mandatory

**@subtitle:** The Subtitle if any

**@creator:** [or @author:] Name of Author

**@subject:** (whatever your subject)

**@description:**

**@keywords:** text document generation processing management latex pdf structured xml citation [your keywords here, used for example by rss feeds, and in sql searches]

**@abstract:** [paper abstract, placed after table of contents]

**@comment:** [...]

**@catalogue:** loc=[Library of Congress classification]; dewey=[Dewey classification]; isbn=[ISBN]; pg=[Project Gutenberg text number]

**@classify\_loc:** [Library of Congress classification]

**@classify\_dewey:** [Dewey classification]

**@classify\_isbn:** [ISBN]

**@classify\_pg:** [Project Gutenberg text number]

**@prefix:** [prefix is placed just after table of contents]

**@prefix\_a:** [prefix is placed just before table of contents - not implemented]

**@prefix\_b:**

**@rcs:** \$Id: sisu\_markup.sst,v 1.2 2007/09/08 17:12:47 ralph Exp \$ [used by rcs or cvs to embed version (revision control) information into document, rcs or cvs can usefully provide a history of updates to a document]

**@structure:** PART; CHAPTER; SECTION; ARTICLE; none; none; optional, document structure can be defined by words to match or regular expression (the regular expression is assumed to start at the beginning of a line of text i.e. *defaultmarkers : A~to : C~and1to6canbeusedwithintextinstead, without this headertag, and may be used to supplement the instructions provided in this headertag if provided* (*@structure : is*

**@level:** newpage=3; breakpage=4

paragraph level, used by latex to breakpages, the page is optional eg. in newpage

**@markup:** information on the markup used, e.g. new=1,2,3; break=4; num\_top=4 [or newpage=1,2,3; breakpage=4; num\_top=4] newpage and breakpage, heading level, used by LaTeX to breakpages. breakpage: starts on a new page in single column text and on a new column in double column text; newpage: starts on a new page for both single and double column texts.

num\_top=4 [auto-number document, starting at level 4. the default is to provide 3 levels, as in 1 level 4, 1.1 level 5, 1.1.1 level 6, markup to be merged within level]

num\_extract [take numbering of headings provided (manually in marked up source document), and use for numbering of segments. Available where a clear numbering structure is provided within document, without the repetition of a number in a header.] [In 0.38 notation, you would map to the equivalent levels, the examples provided would map to the following new=A,B,C; break=1; num\_top=1 [or newpage=A,B,C; breakpage=1; num\_top=1] see headings]

**@bold:** [regular expression of words/phrases to be made bold]

**@italics:** [regular expression of words/phrases to italicise]

**@vocabulary:** name of taxonomy/vocabulary/wordlist to use against document

**@skin:** skin\_doc\_[name\_of\_desired\_document\_skin]

skins change default settings related to the appearance of documents generated, such as the urls of the home site, and the icon/logo for the document or site.

**@links:** { SiSU }http://www.jus.uio.no/sisu/;

{ FSF }http://www.fsf.org

**@promo:** sisu, ruby, search\_libre\_docs, open\_society

places content in right pane in html, makes use of list.yml and promo.yml, commented out sample in document sample:

free\_as\_in\_freedom.richard\_stallman\_crusade\_for\_free\_software.sam\_williams.sst

### 3. Markup of Substantive Text

#### 3.1 Heading Levels

Heading levels are :A~ ,:B~ ,:C~ ,1~ ,2~ ,3~ ... :A - :C being part / section headings, followed by other heading levels, and 1 -6 being headings followed by substantive text or sub-headings. :A~ usually the title :A~ ? conditional level 1 heading (used where a stand-alone document may be imported into another)

**:A~ [heading text]** Top level heading [this usually has similar content to the title @title: ] NOTE: the heading levels described here are in 0.38 notation, see heading

**:B~ [heading text]** Second level heading [this is a heading level divider]

**:C~ [heading text]** Third level heading [this is a heading level divider]

**1~ [heading text]** Top level heading preceding substantive text of document or sub-heading 2, the heading level that would normally be marked 1. or 2. or 3. etc. in a document, and the level on which sisu by default would break html output into named segments, names are provided automatically if none are given (a number), otherwise takes the form 1~my\_filename\_for\_this\_segment

**2~ [heading text]** Second level heading preceding substantive text of document or sub-heading 3, the heading level that would normally be marked 1.1 or 1.2 or 1.3 or 2.1 etc. in a document.

**3~ [heading text]** Third level heading preceding substantive text of document, that would normally be marked 1.1.1 or 1.1.2 or 1.2.1 or 2.1.1 etc. in a document

1~ filename level 1 heading,

% the primary division such as Chapter that is followed by substantive text, and may be further subdivided (this is the level on which by default html segments are made)

### 3.2 Font Attributes

#### markup example:

```
normal text !{emphasis}! *{bold text}* _{underscore}_ /{italics}/ "{citation}" {superscript} {subscript}, +{inserted text} -{strikethrough}-
normal text
!{emphasis}!
*{bold text}*
_{underscore}_
/{italics}/
"{citation}"
{superscript}
,{subscript},
+{inserted text}+
-{strikethrough}-
```

#### resulting output:

```
normal text emphasis bold text underscore italics ;cite¿citation¿/cite¿
superscript subscript inserted text strikethrough

normal text

emphasis

bold text

underscore

italics

;cite¿citation¿/cite¿

superscript

subscript

inserted text

strikethrough
```



### 3.3 Indentation and bullets

#### markup example:

ordinary paragraph

.1 indent paragraph one step

.2 indent paragraph two steps

.9 indent paragraph nine steps

#### resulting output:

ordinary paragraph

indent paragraph one step

indent paragraph two steps

indent paragraph  
nine steps

#### markup example:

\_ \* bullet text

.1 \* bullet text, first indent

.2 \* bullet text, two step indent

#### resulting output:

● bullet text

● bullet text, first indent

● bullet text, two step indent

Numbered List (not to be confused with headings/titles, (document structure))

#### markup example:

# numbered list          numbered list 1., 2., 3, etc.

<=hash; numbered list numbered list indented a., b., c., d., etc.

### 3.4 Footnotes / Endnotes

Footnotes and endnotes not distinguished in markup. They are automatically numbered. Depending on the output file format (html, odf, pdf etc.), the document output selected will have either footnotes or endnotes.

#### markup example:

{ a footnote or endnote }

#### resulting output:

3

#### markup example:

normal text { self contained endnote marker & endnote in one } continues

#### resulting output:

normal text<sup>4</sup> continues

#### markup example:

normal text { \* unnumbered asterisk footnote/endnote, insert multiple asterisks if required } continues

normal text { \*\* another unnumbered asterisk footnote/endnote } continues

#### resulting output:

normal text \* continues

normal text \*\* continues

#### markup example:

normal text [ \* editors notes, numbered asterisk footnote/endnote series ] continues

normal text [ + editors notes, numbered asterisk footnote/endnote series ] continues

#### resulting output:

normal text <sup>\*1</sup> continues

<sup>3</sup> a footnote or endnote

<sup>4</sup> self contained endnote marker and endnote in one

\* unnumbered asterisk footnote/endnote, insert multiple asterisks if required

\*\* another unnumbered asterisk footnote/endnote

normal text <sup>+1</sup> continues

### Alternative endnote pair notation for footnotes/endnotes:

% note the endnote marker "

the standard and pair notation cannot be mixed in the same document

## 3.5 Links

### 3.5.1 Naked URLs within text, dealing with urls

urls are found within text and marked up automatically. A url within text is automatically hyperlinked to itself and by default decorated with angled braces, unless they are contained within a code block (in which case they are passed as normal text), or escaped by a preceding underscore (in which case the decoration is omitted).

#### markup example:

normal text <http://www.jus.uio.no/sisu> continues

#### resulting output:

normal text <<http://www.jus.uio.no/sisu>> continues

An escaped url without decoration

#### markup example:

normal text <http://www.jus.uio.no/sisu> continues

deb <http://www.jus.uio.no/sisu/archive> unstable main non-free

#### resulting output:

normal text <http://www.jus.uio.no/sisu> continues

deb <http://www.jus.uio.no/sisu/archive> unstable main non-free

where a code block is used there is neither decoration nor hyperlinking,

<sup>\*1</sup> editors notes, numbered asterisk footnote/endnote series

<sup>+1</sup> editors notes, numbered asterisk footnote/endnote series

code blocks are discussed later in this document

#### resulting output:

deb <http://www.jus.uio.no/sisu/archive> unstable main non-free

deb-src <http://www.jus.uio.no/sisu/archive> unstable main non-free

To link text or an image to a url the markup is as follows

#### markup example:

about { SiSU }<http://url.org> markup

### 3.5.2 Linking Text

#### resulting output:

about [SiSU](#) markup

A shortcut notation is available so the url link may also be provided automatically as a footnote

#### markup example:

about {

#### resulting output:

about [SiSU](#)<sup>5</sup> markup

### 3.5.3 Linking Images

#### markup example:

{tux.png 64x80 }image

% various url linked images

{tux.png 64x80 "a better way" }<http://www.jus.uio.no/sisu/>

{GnuDebianLinuxRubyBetterWay.png 100x101 "Way Better - with Gnu/Linux, Debian and Ruby"}<http://www.jus.uio.no/sisu/>

{

#### resulting output:

<sup>5</sup> <<http://www.jus.uio.no/sisu/>>

178



179



Gnu/Linux - a better way

180

[ ruby\_logo (png missing) ] <sup>6</sup>

181



Way Better - with Gnu/Linux, Debian and Ruby

182

**linked url footnote shortcut**

183

{  
text marker \*ñame

185

note at a heading level the same is automatically achieved by providing names to headings 1, 2 and 3 i.e. 2[*name*] and 3[*name*] or in the case of auto-heading numbering, without further intervention.

186

**3.6 Grouped Text**

**3.6.1 Tables**

187

Tables may be prepared in two either of two forms

188

**markup example:**

189

```
table{ c3; 40; 30; 30;  
This is a table  
this would become column two of row one  
column three of row one is here  
And here begins another row  
column two of row two  
column three of row two, and so on  
}table
```

190

**resulting output:**

191

This is a table	this would become column two of row one	column three of row one is here
And here begins another row	column two of row two	column three of row two, and so on

192

a second form may be easier to work with in cases where there is not much information in each column

193

**markup example:** <sup>7</sup>

194

!\_ Table 3.1: Contributors to Wikipedia, January 2001 - June 2005

{table~ h 24; 12; 12; 12; 12; 12; 12; 12;}

	Jan. 2001	Jan. 2002	Jan. 2003	Jan. 2004	July 2004	June 2006
Contributors*	10	472	2,188	9,653	25,011	48,721
Active contributors**	9	212	846	3,228	8,442	16,945
Very active contributors***	0	31	190	692	1,639	3,016
No. of English language articles	25	16,000	101,000	190,000	320,000	630,000
No. of articles, all languages	25	19,000	138,000	490,000	862,000	1,600,000

Contributed at least ten times; \* at least 5 times in last month; \* more than 100 times in last month.

195

**resulting output:**

196

<sup>6</sup> <<http://www.ruby-lang.org/en/>>  
<sup>7</sup> Table from the Wealth of Networks by Yochai Benkler  
<[http://www.jus.uio.no/sisu/the\\_wealth\\_of\\_networks.yochai\\_benkler](http://www.jus.uio.no/sisu/the_wealth_of_networks.yochai_benkler)>

197  
198

**Table 3.1: Contributors to Wikipedia, January 2001 - June 2005**

	Jan. 2001	Jan. 2002	Jan. 2003	Jan. 2004	July 2004	June 2006
Contributors*	10	472	2,188	9,653	25,011	48,721
Active contributors**	9	212	846	3,228	8,442	16,945
Very active contributors***	0	31	190	692	1,639	3,016
No. of English language articles	25	16,000	101,000	190,000	320,000	630,000
No. of articles, all languages	25	19,000	138,000	490,000	862,000	1,600,000

199

\* Contributed at least ten times; \*\* at least 5 times in last month; \*\*\* more than 100 times in last month.

200

**3.6.2 Poem**

201  
202

**basic markup:**

```
poem{
  Your poem here
}poem
```

Each verse in a poem is given a separate object number.

203  
204

**markup example:**

```
poem{
  'Fury said to a
  mouse, That he
  met in the
  house,
  "Let us
  both go to
  law: I will
  prosecute
  YOU. -Come,
  I'll take no
  denial; We
  must have a
  trial: For
  really this
  morning I've
  nothing
```

to do.”  
Said the  
mouse to the  
cur, "Such  
a trial,  
dear Sir,  
With  
no jury  
or judge,  
would be  
wasting  
our  
breath.”  
"I'll be  
judge, I'll  
be jury,”  
Said  
cunning  
old Fury:  
"I'll  
try the  
whole  
cause,  
and  
condemn  
you  
to  
death.””

}poem

**resulting output:**

‘Fury said to a  
mouse, That he  
met in the  
house,  
“Let us  
both go to

205  
206

law: I will  
 prosecute  
 YOU. –Come,  
 I’ll take no  
 denial; We  
 must have a  
 trial: For  
 really this  
 morning I’ve  
 nothing  
 to do.”

Said the  
 mouse to the  
 cur, “Such  
 a trial,  
 dear Sir,  
 With  
 no jury  
 or judge,  
 would be  
 wasting  
 our  
 breath.”  
 “I’ll be  
 judge, I’ll  
 be jury,”  
 Said  
 cunning

old Fury:  
 “I’ll  
 try the  
 whole  
 cause,  
 and  
 condemn  
 you  
 to  
 death.””

### 3.6.3 Group

207

#### basic markup:

208

```
group{
```

209

```
  Your grouped text here
```

```
}group
```

A group is treated as an object and given a single object number.

#### markup example:

210

```
group{
```

211

```
  'Fury said to a
```

```
  mouse, That he
```

```
  met in the
```

```
  house,
```

```
  "Let us
```

```
  both go to
```

```
  law: I will
```

```
  prosecute
```

```
  YOU. –Come,
```

```
  I’ll take no
```

```
  denial; We
```

```
  must have a
```

```
  trial: For
```

really this  
 morning I've  
 nothing  
 to do.”  
 Said the  
 mouse to the  
 cur, ”Such  
 a trial,  
 dear Sir,  
 With  
 no jury  
 or judge,  
 would be  
 wasting  
 our  
 breath.”  
 ”I'll be  
 judge, I'll  
 be jury,”  
 Said  
 cunning  
 old Fury:  
 ”I'll  
 try the  
 whole  
 cause,  
 and  
 condemn  
 you  
 to  
 death.””

}group

## resulting output:

‘Fury said to a  
 mouse, That he  
 met in the  
 house,

“Let us  
 both go to  
 law: I will  
 prosecute  
 YOU. –Come,  
 I'll take no  
 denial; We  
 must have a  
 trial: For  
 really this  
 morning I've  
 nothing  
 to do.”  
 Said the  
 mouse to the  
 cur, “Such  
 a trial,  
 dear Sir,  
 With  
 no jury  
 or judge,  
 would be  
 wasting  
 our  
 breath.”  
 “I'll be  
 judge, I'll  
 be jury,”

212  
 213

Said  
cunning  
old Fury:  
“I’ll  
try the  
whole  
cause,  
and  
condemn  
you  
to  
death.””

prosecute  
YOU. –Come,  
I’ll take no  
denial; We  
must have a  
trial: For  
really this  
morning I’ve  
nothing  
to do.”  
Said the  
mouse to the  
cur, “Such  
a trial,  
dear Sir,  
With  
no jury  
or judge,  
would be  
wasting  
our  
breath.”  
“I’ll be  
judge, I’ll  
be jury,”  
Said  
cunning  
old Fury:  
“I’ll  
try the  
whole  
cause,  
and  
condemn  
you  
to  
death.””

### 214 3.6.4 Code

215 Code tags are used to escape regular sisu markup, and have been used extensively within this document to provide examples of **SiSU** markup. You cannot however use code tags to escape code tags. They are however used in the same way as group or poem tags.

216 A code-block is treated as an object and given a single object number. [an option to number each line of code may be considered at some later time]

#### 217 use of code tags instead of poem compared, resulting output:

218 ‘Fury said to a  
mouse, That he  
met in the  
house,  
”Let us  
both go to  
law: I will

## 4. Composite documents markup

It is possible to build a document by creating a master document that requires other documents. The documents required may be complete documents that could be generated independently, or they could be markup snippets, prepared so as to be easily available to be placed within another text. If the calling document is a master document (built from other documents), it should be named with the suffix **.ssm**. Within this document you would provide information on the other documents that should be included within the text. These may be other documents that would be processed in a regular way, or markup bits prepared only for inclusion within a master document **.sst** regular markup file, or **.ssi** (insert/information). A secondary file of the composite document is built prior to processing with the same prefix and the suffix **..sst**.

basic markup for importing a document into a master document

```
<< |filename1.sst|@|^j
<< |filename2.ssi|@|^j
```

The form described above should be relied on. Within the Vim editor it results in the text thus linked becoming hyperlinked to the document it is calling in which is convenient for editing. Alternative markup for importation of documents under consideration, and occasionally supported have been.

```
r{filename}
{filename.ssi}require
<< {filename.ssi}
% using textlink alternatives
|filename.ssi|@|^jrequire
<< |filename.ssi|@|^j
% using thlnk alternatives
<url:filename.ssi>require
<< <url:filename.ssi>
```



## MARKUP SYNTAX HISTORY

### 5. Notes related to Files-types and Markup Syntax

0.38 is substantially current, depreciated 0.16 supported, though file names were changed at 0.37 227

**0.52** (2007w14/6) declared document type identifier at start of text/document: 228

**SiSU** 0.52 229

or, backward compatible using the comment marker: 230

**% SiSU** 0.38 231

variations include ‘**SiSU** (text|master|insert) [version]’ and ‘sisu-[version]’ 232

**0.51** (2007w13/6) skins changed (simplified), markup unchanged 233

**0.42** (2006w27/4) \* (asterisk) type endnotes, used e.g. in relation to author 234

**0.38** (2006w15/7) introduced new/alternative notation for headers, e.g. @title: (instead of 0~ title), and accompanying document structure markup, :A,:B,:C,1,2,3 (maps to previous 1,2,3,4,5,6) 235

**0.37** (2006w09/7) introduced new file naming convention, .sst (text), .ssm (master), .ssi (insert), markup syntax unchanged 236

**0.35** (2005w52/3) sisupod, zipped content file introduced 237

**0.23** (2005w36/2) utf-8 for markup file 238

**0.22** (2005w35/3) image dimensions may be omitted if rmagick is available to be relied upon 239

**0.20.4** (2005w33/4) header 0~ links 240

**0.16** (2005w25/2) substantial changes introduced to make markup cleaner, header 0~ title type, and headings [1-6]~ introduced, also percentage sign (%) at start of a text line as comment marker 241

**DOCUMENT INFORMATION (METADATA)**Generated by: SiSU 0.59.0 of 2007w38/0 (2007-09-23)Ruby version: ruby 1.8.6 (2007-06-07 patchlevel 36) [i486-linux]**Metadata**

Document Manifest @

<[http://www.jus.uio.no/sisu/sisu\\_manual/sisu\\_markup/sisu\\_manifest.html](http://www.jus.uio.no/sisu/sisu_manual/sisu_markup/sisu_manifest.html)>**Dublin Core (DC)***DC tags included with this document are provided here.*DC Title: SiSU - MarkupDC Creator: Ralph AmissahDC Rights: Copyright (C) Ralph Amissah 2007, part of SiSU documentation, License GPL 3DC Type: informationDC Date created: 2002-08-28DC Date issued: 2002-08-28DC Date available: 2002-08-28DC Date modified: 2007-09-16DC Date: 2007-09-16**Version Information**Sourcefile: sisu\_markup.sstFiletype: SiSU text 0.58Sourcefile Digest, MD5(sisu\_markup.sst)= 6848f40f5844e0a7d59dbb86b3ddae92Skin Digest: MD5(/home/ralph/grotto/theatre/dbld/sisu-dev/sisu/data/doc/sisu/sisu\_markup\_samples/sisu\_manual/\_sisu/skin/doc/skin\_sisu\_manual.rb)=  
20fc43cf3eb6590bc3399a1aef65c5a9**Generated**Document (metaverse) last generated: Mon Sep 24 15:32:23 +0100  
2007

## Information on this document copy and an unofficial List of Some web related information and sources

”Support Open Standards and Software Libre for the Information Technology Infrastructure” RA

### Information on this document copy [www.jus.uio.no/sisu/](http://www.jus.uio.no/sisu/)

Generated by SiSU found at [www.jus.uio.no/sisu](http://www.jus.uio.no/sisu) [ SiSU 0.59.0 2007w38/0 ] [www.sisudoc.org](http://www.sisudoc.org).  
SiSU is software for document structuring, publishing and search (using SiSU: object citation numbering, markup, meta-markup, and system) Copyright © 1997, current 2007 Ralph Amissah, All Rights Reserved.

SiSU is released under [GPL 3](http://www.fsf.org/licenses/gpl.html) or later ([www.fsf.org/licenses/gpl.html](http://www.fsf.org/licenses/gpl.html)).

W3 since October 3 1993  SiSU 1997, current 2007.  
SiSU presentations at [www.jus.uio.no/sisu/](http://www.jus.uio.no/sisu/)

SiSU **pdf** versions can be found at:

[http://www.jus.uio.no/sisu/sisu\\_markup/portrait.pdf](http://www.jus.uio.no/sisu/sisu_markup/portrait.pdf)

[http://www.jus.uio.no/sisu/sisu\\_markup/landscape.pdf](http://www.jus.uio.no/sisu/sisu_markup/landscape.pdf)

SiSU **html** versions may be found at:

[http://www.jus.uio.no/sisu/sisu\\_markup/toc.html](http://www.jus.uio.no/sisu/sisu_markup/toc.html) OR

[http://www.jus.uio.no/sisu/sisu\\_markup/doc.html](http://www.jus.uio.no/sisu/sisu_markup/doc.html)

SiSU **Manifest** of document output and metadata may be found at:

[http://www.jus.uio.no/sisu/sisu\\_markup/sisu\\_manifest.html](http://www.jus.uio.no/sisu/sisu_markup/sisu_manifest.html)

SiSU found at: [www.jus.uio.no/sisu/](http://www.jus.uio.no/sisu/)

## Links that may be of interest at SiSU and elsewhere:

SiSU Manual

[http://www.jus.uio.no/sisu/sisu\\_manual/](http://www.jus.uio.no/sisu/sisu_manual/)

Book Samples and Markup Examples

<http://www.jus.uio.no/sisu/SiSU/2.html>

SiSU @ Wikipedia

<http://en.wikipedia.org/wiki/SiSU>

SiSU @ Freshmeat

<http://freshmeat.net/projects/sisu/>

SiSU @ Ruby Application Archive

<http://raa.ruby-lang.org/project/sisu/>

SiSU @ Debian

<http://packages.qa.debian.org/s/sisu.html>

SiSU Download

<http://www.jus.uio.no/sisu/SiSU/download.html>

SiSU Changelog

<http://www.jus.uio.no/sisu/SiSU/changelog.html>

SiSU help

[http://www.jus.uio.no/sisu/sisu\\_manual/sisu\\_help/](http://www.jus.uio.no/sisu/sisu_manual/sisu_help/)

SiSU help sources

[http://www.jus.uio.no/sisu/sisu\\_manual/sisu\\_help\\_sources/](http://www.jus.uio.no/sisu/sisu_manual/sisu_help_sources/)

SiSU home:

[www.jus.uio.no/sisu/](http://www.jus.uio.no/sisu/)