

# SiSU

Markup

Ralph Amissah

copy @ [www.jus.uio.no/sisu/](http://www.jus.uio.no/sisu/) \*

---

Copyright © Ralph Amissah 2007, part of SiSU documentation, License GPL 3

Generated by SiSU [ SiSU 0.59.1 of 2007w39/2 ] [www.jus.uio.no/sisu](http://www.jus.uio.no/sisu)

Copyright © 1997, current 2007 Ralph Amissah, All Rights Reserved.

SiSU is software for document structuring, publishing and search (with object citation numbering), [www.sisudoc.org](http://www.sisudoc.org)

SiSU is released under GPL 3 or later, <<http://www.fsf.org/licenses/gpl.html>>.

Document information:

*sourcefile* [sisu\\_markup.sst](#)

Generated by SiSU [www.jus.uio.no/sisu](http://www.jus.uio.no/sisu)

version information: [SiSU 0.59.1 of 2007w39/2](#)

For alternative output formats of this document check:

<[http://www.jus.uio.no/sisu/sisu\\_markup/sisu\\_manifest.html](http://www.jus.uio.no/sisu/sisu_markup/sisu_manifest.html)>

# Contents

<b>SiSU - Markup, Ralph Amissah</b>	<b>1</b>
<b>SiSU Markup</b>	<b>1</b>
1. Introduction to SiSU Markup . . . . .	2
1.1 Summary . . . . .	2
1.2 Markup Examples . . . . .	2
2. Markup of Headers . . . . .	4
2.1 Sample Header . . . . .	4
2.2 Available Headers . . . . .	4
3. Markup of Substantive Text . . . . .	8
3.1 Heading Levels . . . . .	8
3.2 Font Attributes . . . . .	8
3.3 Indentation and bullets . . . . .	9
3.4 Footnotes / Endnotes . . . . .	10
3.5 Links . . . . .	10
3.6 Grouped Text . . . . .	12
4. Composite documents markup . . . . .	20
<b>Markup Syntax History</b>	<b>21</b>
5. Notes related to Files-types and Markup Syntax . . . . .	22
<b>Document Information (metadata)</b>	<b>23</b>
Metadata . . . . .	23
<b>Information on this document copy and an unofficial List of Some web related information and sources</b>	<b>24</b>
Information on this document copy . . . . .	24
Links that may be of interest . . . . .	24

<b>SISU - MARKUP, RALPH AMISSAH</b>	1
<b>SISU MARKUP</b>	2

## 1. Introduction to SiSU Markup<sup>1</sup>

### 1.1 Summary

SiSU source documents are plaintext (UTF-8)<sup>2</sup> files

All paragraphs are separated by an empty line.

Markup is comprised of:

- at the top of a document, the document header made up of semantic meta-data about the document and if desired additional processing instructions (such an instruction to automatically number headings from a particular level down)
- followed by the prepared substantive text of which the most important single characteristic is the markup of different heading levels, which define the primary outline of the document structure. Markup of substantive text includes:
  - heading levels defines document structure
  - text basic attributes, italics, bold etc.
  - grouped text (objects), which are to be treated differently, such as code blocks or poems.
  - footnotes/endnotes
  - linked text and images
  - paragraph actions, such as indent, bulleted, numbered-lists, etc.

Some interactive help on markup is available, by typing `sisu` and selecting `markup` or `sisu -help markup`

### 1.2 Markup Examples

#### 1.2.1 Online

Online markup examples are available together with the respective outputs produced from `<http://www.jus.uio.no/sisu/SiSU/2.html>` or from `<http://www.jus.uio.no/sisu/sisu_examples/>`

There is of course this document, which provides a cursory overview of `sisu` markup and the respective output produced: `<http://www.jus.uio.no/sisu/sisu_markup/>`

Some example marked up files are available as `html` with syntax highlighting for viewing: `<http://www.jus.uio.no/sisu/sample/syntax>`

an alternative presentation of markup syntax: `<http://www.jus.uio.no/sisu/sample/on_markup.txt>`

---

<sup>1</sup> From sometime after SiSU 0.58 it should be possible to describe SiSU markup using SiSU, which though not an original design goal is useful.

<sup>2</sup> files should be prepared using UTF-8 character encoding

### 1.2.2 Installed

23

With **SiSU** installed sample skins may be found in: `/usr/share/doc/sisu/sisu_markup_samples/dfsg`<sup>24</sup> (or equivalent directory) and if `sisu-markup-samples` is installed also under: `/usr/share/doc/sisu/sisu_markup_sa`  
free

## 2. Markup of Headers

Headers consist of semantic meta-data about a document, which can be used by any output module of the program; and may in addition include extra processing instructions.

Note: the first line of a document may include information on the markup version used in the form of a comment. Comments are a percentage mark at the start of a paragraph (and as the first character in a line of text) followed by a space and the comment:

```
% this would be a comment
```

### 2.1 Sample Header

This current document has a header similar to this one (without the comments):

```
% SiSU 0.57
@title: SiSU
@subtitle: Markup
@creator: Ralph Amissah
@rights: Copyright (C) Ralph Amissah 2007, part of SiSU documentation, License GPL 3
@type: information
@subject: ebook, epubliing, electronic book, electronic publishing, electronic document, electronic citation, data structure, citation systems,
search
@date.created: 2002-08-28
@date.issued: 2002-08-28
@date.available: 2002-08-28
@date.modified: 2007-09-16
@date: 2007-09-16
@level: new=C; break=1; num_top=1
% comment: in this @level header num_top=1 starts automatic heading numbering at heading level 1 (numbering continues 3 levels down);
the new and break instructions are used by the LaTeX/pdf and odf output to determine where to put page breaks (that are not used by html
output or say sql database population).
@skin: skin_sisu_manual
% skins modify the appearance of a document and are placed in a sub-directory under ./sisu/skin ~ /sisu/skin or /etc/sisu/skin. A skin may
affect single documents that request them, all documents in a directory, or be site-wide. (A document is affected by a single skin)
@bold: /Gnu|Debian|Ruby|SiSU/
@links: { SiSU Manual }http://www.jus.uio.no/sisu/sisu_manual/
{ Book Samples and Markup Examples }http://www.jus.uio.no/sisu/SiSU/2.html
{ SiSU @ Wikipedia }http://en.wikipedia.org/wiki/SiSU
{ SiSU @ Freshmeat }http://freshmeat.net/projects/sisu/
{ SiSU @ Ruby Application Archive }http://raa.ruby-lang.org/project/sisu/
{ SiSU @ Debian }http://packages.qa.debian.org/s/sisu.html
{ SiSU Download }http://www.jus.uio.no/sisu/SiSU/download.html
{ SiSU Changelog }http://www.jus.uio.no/sisu/SiSU/changelog.html
```

### 2.2 Available Headers

Header tags appear at the beginning of a document and provide meta information on the document (such as the Dublin Core), or information as to how the document as a whole is to be processed. All header instructions take either the form @headname: or 0~ headname. All Dublin Core meta tags are available

**@identifier:** information or instructions

where the “identifier” is a tag recognised by the program, and the “information” or “instructions” belong to the tag/identifier specified 35

Note: a header where used should only be used once; all headers apart from @title: are optional; the @structure: header is used to describe document structure, and can be useful to know. 36

This is a sample header 37

**% SiSU 0.38** [declared file-type identifier with markup version] 38

**@title:** [title text] This is the title of the document and used as such, this header is the only one that is mandatory 39

**@subtitle:** The Subtitle if any 40

**@creator:** [or @author:] Name of Author 41

**@subject:** (whatever your subject) 42

**@description:** 43

**@publisher:** 44

**@contributor:** 45

**@translator:** [or @translated\_by:] 46

**@illustrator:** [or @illustrated\_by:] 47

**@prepared\_by:** [or @digitized\_by:] 48

**@date: 2000-08-27** [ also @date.created: @date.issued: @date.available: @date.valid: @date.modified: ] 49

**@type: article** 50

**@format:** 51

**@identifier:** 52

**@source:** 53

**@language:** [or @language.document:] [country code for language if available, or language, English, en is the default setting] (en - English, fr - French, de - German, it - Italian, es - Spanish, pt - Portuguese, sv - Swedish, da - Danish, fi - Finnish, no - Norwegian, is - Icelandic, nl - Dutch, et - Estonian, hu - Hungarian, pl - Polish, ro - Romanian, ru - Russian, el - Greek, uk - Ukranian, tr - Turkish, sk - Slovak, sl - Slovenian, hr - Croatian, cs - Czech, bg - Bulgarian ) [however, encodings are not available for all of the languages listed.] 54

[@language.original: original language in which the work was published] 55

**@papersize:** (A4|US\_letter|book\_B5|book\_A5|US\_legal) 56

**@relation:** 57

**@coverage:** 58

**@rights:** Copyright (c) Name of Right Holder, all rights reserved, or as granted: public domain, copyleft, creative commons variant, etc. 59

**@owner:** 60



<b>@keywords:</b> text document generation processing management latex pdf structured xml citation [your keywords here, used for example by rss feeds, and in sql searches]	61
<b>@abstract:</b> [paper abstract, placed after table of contents]	62
<b>@comment:</b> [...]	63
<b>@catalogue:</b> loc=[Library of Congress classification]; dewey=[Dewey classification]; isbn=[ISBN]; pg=[Project Gutenberg text number]	64
<b>@classify_loc:</b> [Library of Congress classification]	65
<b>@classify_dewey:</b> [Dewey classification]	66
<b>@classify_isbn:</b> [ISBN]	67
<b>@classify_pg:</b> [Project Gutenberg text number]	68
<b>@prefix:</b> [prefix is placed just after table of contents]	69
<b>@prefix_a:</b> [prefix is placed just before table of contents - not implemented]	70
<b>@prefix_b:</b>	71
<b>@rcs:</b> \$Id: sisu_markup.sst,v 1.2 2007/09/08 17:12:47 ralph Exp \$ [used by rcs or cvs to embed version (revision control) information into document, rcs or cvs can usefully provide a history of updates to a document ]	72
<b>@structure:</b> PART; CHAPTER; SECTION; ARTICLE; none; none; optional, document structure can be defined by words to match or regular expression (the regular expression is assumed to start at the beginning of a line of text i.e. <i>defaultmarkers : A~to : C~and1fo6canbeusedwithintextinstead, withoutthisheadertag, andmaybeusedtosupplementtheinstructions</i> )	73
<b>@level:</b> newpage=3; breakpage=4 paragraph level, used by latex to breakpages, the page is optional eg. in newpage	74
<b>@markup:</b> information on the markup used, e.g. new=1,2,3; break=4; num_top=4 [or newpage=1,2,3; breakpage=4; num_top=4] newpage and breakpage, heading level, used by LaTeX to breakpages. breakpage: starts on a new page in single column text and on a new column in double column text; newpage: starts on a new page for both single and double column texts. num_top=4 [auto-number document, starting at level 4. the default is to provide 3 levels, as in 1 level 4, 1.1 level 5, 1.1.1 level 6, markup to be merged within level] num_extract [take numbering of headings provided (manually in marked up source document), and use for numbering of segments. Available where a clear numbering structure is provided within document, without the repetition of a number in a header.] [In 0.38 notation, you would map to the equivalent levels, the examples provided would map to the following new=A,B,C; break=1; num_top=1 [or newpage=A,B,C; breakpage=1; num_top=1] see headings]	75
<b>@bold:</b> [regular expression of words/phrases to be made bold]	76
<b>@italics:</b> [regular expression of words/phrases to italicise]	77
<b>@vocabulary:</b> name of taxonomy/vocabulary/wordlist to use against document	78
<b>@skin:</b> skin_doc_[name_of_desired_document_skin]	79

skins change default settings related to the appearance of documents generated, such as the urls of the home site, and the icon/logo for the document or site.

**@links:** { **SiSU** }<http://www.jus.uio.no/sisu/>; 80  
{ **FSF** }<http://www.fsf.org>

**@promo:** sisu, ruby, search\_libre\_docs, open\_society 81  
places content in right pane in html, makes use of list.yml and promo.yml, commented out sample in document sample: free\_as\_in\_freedom.richard\_stallman\_crusade\_for\_free\_software.sam\_williams.sst

### 3. Markup of Substantive Text

82

#### 3.1 Heading Levels

83

Heading levels are :A~ ,:B~ ,:C~ ,1~ ,2~ ,3~ ... :A - :C being part / section headings, followed by other heading levels, and 1 -6 being headings followed by substantive text or sub-headings. :A~ usually the title :A~ ? conditional level 1 heading (used where a stand-alone document may be imported into another)

84

:A~ **[heading text]** Top level heading [this usually has similar content to the title @title: ]  
NOTE: the heading levels described here are in 0.38 notation, see heading

85

:B~ **[heading text]** Second level heading [this is a heading level divider]

86

:C~ **[heading text]** Third level heading [this is a heading level divider]

87

1~ **[heading text]** Top level heading preceding substantive text of document or sub-heading 2, the heading level that would normally be marked 1. or 2. or 3. etc. in a document, and the level on which sisu by default would break html output into named segments, names are provided automatically if none are given (a number), otherwise takes the form 1~my\_filename\_for\_this\_segment

88

2~ **[heading text]** Second level heading preceding substantive text of document or sub-heading 3, the heading level that would normally be marked 1.1 or 1.2 or 1.3 or 2.1 etc. in a document.

89

3~ **[heading text]** Third level heading preceding substantive text of document, that would normally be marked 1.1.1 or 1.1.2 or 1.2.1 or 2.1.1 etc. in a document

90

1~ filename level 1 heading,

91

% the primary division such as Chapter that is followed by substantive text, and may be further subdivided (this is the level on which by default html segments are made)

#### 3.2 Font Attributes

92

##### markup example:

93

```
normal text !{emphasis}! *{bold text}* _{underscore}_ /{italics}/ "{citation}" {superscript}{subscript},+{insertedtext}+
normal text
!{emphasis}!
*{bold text}*
_{underscore}_
/{italics}/
"{citation}"
{superscript}
,{subscript},
+{inserted text}+
-{strikethrough}-
```

94

##### resulting output:

95

normal text **emphasis** **bold text** underscore *italics* ;cite¿citation¿/cite¿ <sup>superscript</sup> subscript  
inserted text ~~strikethrough~~

96

normal text

97

<b>emphasis</b>	98
<b>bold text</b>	99
<u>underscore</u>	100
<i>italics</i>	101
<code>&lt;cite&gt;{citation}&lt;/cite&gt;</code>	102
superscript	103
subscript	104
<u>inserted text</u>	105
<del>strikethrough</del>	106

### 3.3 Indentation and bullets 107

<b>markup example:</b>	108
ordinary paragraph	109

.1 indent paragraph one step  
.2 indent paragraph two steps  
.9 indent paragraph nine steps

<b>resulting output:</b>	110
--------------------------	-----

ordinary paragraph	111
indent paragraph one step	112
indent paragraph two steps	113
indent paragraph nine steps	114

<b>markup example:</b>	115
_* bullet text	116

.1\* bullet text, first indent  
.2\* bullet text, two step indent

<b>resulting output:</b>	117
--------------------------	-----

● bullet text	118
● bullet text, first indent	119
● bullet text, two step indent	120

Numbered List (not to be confused with headings/titles, (document structure))	121
---	-----

<b>markup example:</b>	122
# numbered list          numbered list 1., 2., 3, etc.	123

<=hash> numbered list numbered list indented a., b., c., d., etc.

### 3.4 Footnotes / Endnotes

Footnotes and endnotes not distinguished in markup. They are automatically numbered. Depending on the output file format (html, odf, pdf etc.), the document output selected will have either footnotes or endnotes.

#### markup example:

{ a footnote or endnote }

#### resulting output:

3

#### markup example:

normal text { self contained endnote marker & endnote in one } continues

#### resulting output:

normal text<sup>4</sup> continues

#### markup example:

normal text { \* unnumbered asterisk footnote/endnote, insert multiple asterisks if required } continues

normal text { \*\* another unnumbered asterisk footnote/endnote } continues

#### resulting output:

normal text \* continues

normal text \*\* continues

#### markup example:

normal text [ \* editors notes, numbered asterisk footnote/endnote series ] continues

normal text [ + editors notes, numbered asterisk footnote/endnote series ] continues

#### resulting output:

normal text <sup>\*1</sup> continues

normal text <sup>+1</sup> continues

#### Alternative endnote pair notation for footnotes/endnotes:

% note the endnote marker "

the standard and pair notation cannot be mixed in the same document

### 3.5 Links

#### 3.5.1 Naked URLs within text, dealing with urls

urls are found within text and marked up automatically. A url within text is automatically

<sup>3</sup> a footnote or endnote

<sup>4</sup> self contained endnote marker and endnote in one

\* unnumbered asterisk footnote/endnote, insert multiple asterisks if required

\*\* another unnumbered asterisk footnote/endnote

<sup>\*1</sup> editors notes, numbered asterisk footnote/endnote series

<sup>+1</sup> editors notes, numbered asterisk footnote/endnote series

hyperlinked to itself and by default decorated with angled braces, unless they are contained within a code block (in which case they are passed as normal text), or escaped by a preceding underscore (in which case the decoration is omitted).

**markup example:**

normal text `http://www.jus.uio.no/sisu continues`

**resulting output:**

normal text `<http://www.jus.uio.no/sisu> continues`

An escaped url without decoration

**markup example:**

normal text `http://www.jus.uio.no/sisu continues`

deb `http://www.jus.uio.no/sisu/archive unstable main non-free`

**resulting output:**

normal text `http://www.jus.uio.no/sisu continues`

deb `http://www.jus.uio.no/sisu/archive unstable main non-free`

where a code block is used there is neither decoration nor hyperlinking, code blocks are discussed later in this document

**resulting output:**

deb `http://www.jus.uio.no/sisu/archive unstable main non-free`

deb-src `http://www.jus.uio.no/sisu/archive unstable main non-free`

To link text or an image to a url the markup is as follows

**markup example:**

about { SiSU }`http://url.org markup`

### 3.5.2 Linking Text

**resulting output:**

about SiSU markup

A shortcut notation is available so the url link may also be provided automatically as a footnote

**markup example:**

about {

**resulting output:**

about SiSU<sup>5</sup> markup

### 3.5.3 Linking Images

**markup example:**

---

<sup>5</sup> `<http://www.jus.uio.no/sisu/>`

```
{tux.png 64x80 }image
% various url linked images
{tux.png 64x80 "a better way" }http://www.jus.uio.no/sisu/
{GnuDebianLinuxRubyBetterWay.png 100x101 "Way Better - with Gnu/Linux, Debian and Ruby" }http://www.jus.uio.no/sisu/
{
```

**resulting output:**

Gnu/Linux - a better way

[ ruby\_logo (png missing) ] <sup>6</sup>



Way Better - with Gnu/Linux, Debian and Ruby

**linked url footnote shortcut**

```
{
text marker *ñame
```

note at a heading level the same is automatically achieved by providing names to headings 1, 2 and 3 i.e. 2[ñame] and 3[ñame] or in the case of auto-heading numbering, without further intervention.

**3.6 Grouped Text****3.6.1 Tables**

Tables may be prepared in two either of two forms

**markup example:**

```
table{ c3; 40; 30; 30;
```

---

<sup>6</sup> <<http://www.ruby-lang.org/en/>>

This is a table  
 this would become column two of row one  
 column three of row one is here  
 And here begins another row  
 column two of row two  
 column three of row two, and so on  
 }table

### resulting output:

This is a table  
 And here begins another row

this would become column two of row one  
 column two of row two

column three of row one is here  
 column three of row two, and so on

a second form may be easier to work with in cases where there is not much information in each column

### markup example: <sup>7</sup>

!\_ Table 3.1: Contributors to Wikipedia, January 2001 - June 2005

{table~ h 24; 12; 12; 12; 12; 12; 12; }

|Jan. 2001|Jan. 2002|Jan. 2003|Jan. 2004|July 2004|June 2006

Contributors\* | 10| 472| 2,188| 9,653| 25,011| 48,721

Active contributors\*\* | 9| 212| 846| 3,228| 8,442| 16,945

Very active contributors\*\*\* | 0| 31| 190| 692| 1,639| 3,016

No. of English language articles| 25| 16,000| 101,000| 190,000| 320,000| 630,000

No. of articles, all languages | 25| 19,000| 138,000| 490,000| 862,000|1,600,000

Contributed at least ten times; \* at least 5 times in last month; \* more than 100 times in last month.

### resulting output:

**Table 3.1: Contributors to Wikipedia, January 2001 - June 2005**

	Jan. 2001	Jan. 2002	Jan. 2003	Jan. 2004	July 2004	June 2006
Contributors*	10	472	2,188	9,653	25,011	48,721
Active contributors**	9	212	846	3,228	8,442	16,945
Very active contributors***	0	31	190	692	1,639	3,016
No. of English language articles	25	16,000	101,000	190,000	320,000	630,000
No. of articles, all languages	25	19,000	138,000	490,000	862,000	1,600,000

\* Contributed at least ten times; \*\* at least 5 times in last month; \*\*\* more than 100 times in last month.

## 3.6.2 Poem

### basic markup:

poem{

Your poem here

}poem

Each verse in a poem is given a separate object number.

### markup example:

poem{

'Fury said to a

<sup>7</sup> Table from the Wealth of Networks by Yochai Benkler  
 <[http://www.jus.uio.no/sisu/the\\_wealth\\_of\\_networks.yochai\\_benkler](http://www.jus.uio.no/sisu/the_wealth_of_networks.yochai_benkler)>



mouse, That he  
met in the  
house,  
"Let us  
both go to  
law: I will  
prosecute  
YOU. –Come,  
I'll take no  
denial; We  
must have a  
trial: For  
really this  
morning I've  
nothing  
to do."  
Said the  
mouse to the  
cur, "Such  
a trial,  
dear Sir,  
With  
no jury  
or judge,  
would be  
wasting  
our  
breath."  
"I'll be  
judge, I'll  
be jury,"  
Said  
cunning  
old Fury:  
"I'll  
try the  
whole  
cause,  
and  
condemn  
you  
to  
death."

}poem

### resulting output:

'Fury said to a  
mouse, That he  
met in the  
house,  
"Let us

205

206

both go to  
law: I will  
prosecute  
YOU. –Come,  
I'll take no  
denial; We  
must have a  
trial: For  
really this  
morning I've  
nothing  
to do.”  
Said the  
mouse to the  
cur, “Such  
a trial,  
dear Sir,  
With  
no jury  
or judge,  
would be  
wasting  
our  
breath.”  
“I'll be  
judge, I'll  
be jury,”  
Said  
cunning  
old Fury:  
“I'll  
try the  
whole  
cause,  
and  
condemn  
you  
to  
death.””

### 3.6.3 Group

207

#### basic markup:

208

```
group{  
  Your grouped text here  
}group
```

209

A group is treated as an object and given a single object number.

#### markup example:

210

```
group{  
  'Fury said to a  
    mouse, That he  
    met in the  
    house,  
  "Let us  
    both go to  
    law: I will  
    prosecute  
    YOU. –Come,  
    I'll take no  
    denial; We  
    must have a  
    trial: For  
    really this  
    morning I've  
    nothing  
    to do."  
  Said the  
    mouse to the  
    cur, "Such  
    a trial,  
    dear Sir,  
    With  
    no jury  
    or judge,  
    would be  
    wasting  
    our  
    breath."  
  "I'll be  
    judge, I'll  
    be jury,"  
    Said  
    cunning  
    old Fury:  
  "I'll  
    try the  
    whole  
    cause,  
    and  
    condemn  
    you  
    to
```

211

death.”

}group

**resulting output:**

‘Fury said to a  
mouse, That he  
met in the  
house,  
“Let us  
both go to  
law: I will  
prosecute  
YOU. –Come,  
I’ll take no  
denial; We  
must have a  
trial: For  
really this  
morning I’ve  
nothing  
to do.”  
Said the  
mouse to the  
cur, “Such  
a trial,  
dear Sir,  
With  
no jury  
or judge,  
would be  
wasting  
our  
breath.”  
“I’ll be  
judge, I’ll  
be jury,”  
Said  
cunning  
old Fury:

212

213

“I’ll  
try the  
whole  
cause,  
and  
condemn  
you  
to  
death.””

### 3.6.4 Code

214

Code tags are used to escape regular sisu markup, and have been used extensively within this document to provide examples of **SiSU** markup. You cannot however use code tags to escape code tags. They are however used in the same way as group or poem tags.

215

A code-block is treated as an object and given a single object number. [an option to number each line of code may be considered at some later time]

216

#### use of code tags instead of poem compared, resulting output:

217

’Fury said to a  
mouse, That he  
met in the  
house,  
”Let us  
both go to  
law: I will  
prosecute  
YOU. –Come,  
I’ll take no  
denial; We  
must have a  
trial: For  
really this  
morning I’ve  
nothing  
to do.”  
Said the  
mouse to the  
cur, ”Such  
a trial,  
dear Sir,  
With  
no jury  
or judge,  
would be  
wasting  
our

218

breath.”  
“I’ll be  
judge, I’ll  
be jury,”  
Said  
cunning  
old Fury:  
“I’ll  
try the  
whole  
cause,  
and  
condemn  
you  
to  
death.””

## 4. Composite documents markup

219

It is possible to build a document by creating a master document that requires other documents. The documents required may be complete documents that could be generated independently, or they could be markup snippets, prepared so as to be easily available to be placed within another text. If the calling document is a master document (built from other documents), it should be named with the suffix **.ssm**. Within this document you would provide information on the other documents that should be included within the text. These may be other documents that would be processed in a regular way, or markup bits prepared only for inclusion within a master document **.sst** regular markup file, or **.ssi** (insert/information). A secondary file of the composite document is built prior to processing with the same prefix and the suffix **.sst**.

220

basic markup for importing a document into a master document

221

```
<< |filename1.sst|@|j
```

222

```
<< |filename2.ssi|@|j
```

The form described above should be relied on. Within the Vim editor it results in the text thus linked becoming hyperlinked to the document it is calling in which is convenient for editing. Alternative markup for importation of documents under consideration, and occasionally supported have been.

223

```
r{filename}  
{filename.ssi}require  
<< {filename.ssi}  
% using textlink alternatives  
|filename.ssi|@|jrequire  
<< |filename.ssi|@|j  
% using thlnk alternatives  
<url:filename.ssi>require  
<< <url:filename.ssi>
```

224

## MARKUP SYNTAX HISTORY

225



## 5. Notes related to Files-types and Markup Syntax

- 0.38 is substantially current, depreciated 0.16 supported, though file names were changed at 0.37 227
- 0.52** (2007w14/6) declared document type identifier at start of text/document: 228  
**SiSU** 0.52 229
- or, backward compatible using the comment marker: 230  
**% SiSU** 0.38 231
- variations include '**SiSU** (text|master|insert) [version]' and 'sisu-[version]' 232
- 0.51** (2007w13/6) skins changed (simplified), markup unchanged 233
- 0.42** (2006w27/4) \* (asterisk) type endnotes, used e.g. in relation to author 234
- 0.38** (2006w15/7) introduced new/alternative notation for headers, e.g. @title: (instead of 0~ title), and accompanying document structure markup, :A,:B,:C,1,2,3 (maps to previous 1,2,3,4,5,6) 235
- 0.37** (2006w09/7) introduced new file naming convention, .sst (text), .ssm (master), .ssi (insert), markup syntax unchanged 236
- 0.35** (2005w52/3) sisupod, zipped content file introduced 237
- 0.23** (2005w36/2) utf-8 for markup file 238
- 0.22** (2005w35/3) image dimensions may be omitted if rmagick is available to be relied upon 239
- 0.20.4** (2005w33/4) header 0~ links 240
- 0.16** (2005w25/2) substantial changes introduced to make markup cleaner, header 0~ title type, and headings [1-6]~ introduced, also percentage sign (%) at start of a text line as comment marker 241

## DOCUMENT INFORMATION (METADATA)

### Metadata

Document Manifest @

<[http://www.jus.uio.no/sisu/sisu\\_manual/sisu\\_markup/sisu\\_manifest.html](http://www.jus.uio.no/sisu/sisu_manual/sisu_markup/sisu_manifest.html)>

### Dublin Core (DC)

*DC tags included with this document are provided here.*

DC Title: SiSU - Markup

DC Creator: Ralph Amissah

DC Rights: Copyright (C) Ralph Amissah 2007, part of SiSU documentation, License GPL 3

DC Type: information

DC Date created: 2002-08-28

DC Date issued: 2002-08-28

DC Date available: 2002-08-28

DC Date modified: 2007-09-16

DC Date: 2007-09-16

### Version Information

Sourcefile: sisu\_markup.sst

Filetype: SiSU text 0.58

Sourcefile Digest, MD5(sisu\_markup.sst)= 6848f40f5844e0a7d59dbb86b3ddae92

Skin\_Digest: MD5(/home/ralph/grotto/theatre/dbld/builds/sisu/sisu/data/doc/sisu/sisu\_markup\_samples/sisu\_n  
20fc43cf3eb6590bc3399a1aef65c5a9

### Generated

Document (metaverse) last generated: Tue Sep 25 02:53:09 +0100 2007

Generated by: SiSU 0.59.1 of 2007w39/2 (2007-09-25)

Ruby version: ruby 1.8.6 (2007-06-07 patchlevel 36) [i486-linux]

## Information on this document copy and an unofficial List of Some web related information and sources

”Support Open Standards and Software Libre for the Information Technology Infrastructure”  
RA

### Information on this document copy [www.jus.uio.no/sisu/](http://www.jus.uio.no/sisu/)

Generated by SiSU found at [www.jus.uio.no/sisu/](http://www.jus.uio.no/sisu/) [ SiSU 0.59.1 2007w39/2 ] [www.sisudoc.org](http://www.sisudoc.org). SiSU is software for document structuring, publishing and search (using SiSU: object citation numbering, markup, meta-markup, and system) Copyright © 1997, current 2007 Ralph Amissah, All Rights Reserved.

SiSU is released under GPL 3 or later ([www.fsf.org/licenses/gpl.html](http://www.fsf.org/licenses/gpl.html)).

W3 since October 3 1993  SiSU 1997, current 2007.

SiSU presentations at [www.jus.uio.no/sisu/](http://www.jus.uio.no/sisu/)

SiSU **pdf** versions can be found at:

[http://www.jus.uio.no/sisu/sisu\\_markup/portrait.pdf](http://www.jus.uio.no/sisu/sisu_markup/portrait.pdf)

[http://www.jus.uio.no/sisu/sisu\\_markup/landscape.pdf](http://www.jus.uio.no/sisu/sisu_markup/landscape.pdf)

SiSU **html** versions may be found at:

[http://www.jus.uio.no/sisu/sisu\\_markup/toc.html](http://www.jus.uio.no/sisu/sisu_markup/toc.html) OR

[http://www.jus.uio.no/sisu/sisu\\_markup/doc.html](http://www.jus.uio.no/sisu/sisu_markup/doc.html)

SiSU Manifest of document output and metadata may be found at:

[http://www.jus.uio.no/sisu/sisu\\_markup/sisu\\_manifest.html](http://www.jus.uio.no/sisu/sisu_markup/sisu_manifest.html)

SiSU found at: [www.jus.uio.no/sisu/](http://www.jus.uio.no/sisu/)

### Links that may be of interest at SiSU and elsewhere:

SiSU Manual

[http://www.jus.uio.no/sisu/sisu\\_manual/](http://www.jus.uio.no/sisu/sisu_manual/)

Book Samples and Markup Examples

<http://www.jus.uio.no/sisu/SiSU/2.html>

SiSU @ Wikipedia

<http://en.wikipedia.org/wiki/SiSU>

SiSU @ Freshmeat

<http://freshmeat.net/projects/sisu/>

SiSU @ Ruby Application Archive

<http://raa.ruby-lang.org/project/sisu/>

SiSU @ Debian

<http://packages.qa.debian.org/s/sisu.html>

### SiSU Download

<http://www.jus.uio.no/sisu/SiSU/download.html>

### SiSU Changelog

<http://www.jus.uio.no/sisu/SiSU/changelog.html>

### SiSU help

[http://www.jus.uio.no/sisu/sisu\\_manual/sisu\\_help/](http://www.jus.uio.no/sisu/sisu_manual/sisu_help/)

### SiSU help sources

[http://www.jus.uio.no/sisu/sisu\\_manual/sisu\\_help\\_sources/](http://www.jus.uio.no/sisu/sisu_manual/sisu_help_sources/)

### SiSU home:

**[www.jus.uio.no/sisu/](http://www.jus.uio.no/sisu/)**